

Securifor® 4D / A1 rated system

**Certified to LPS 1175 A1
(Formerly SR1), the Securifor®
4D panel with B Thru type of
post with spider fixator offer
flexible and reliable security
against intrusion.**



Systems detail



Benefits

Enhanced Security Certification

Our system is tested and certified according to the LPS 1175 A1 (Formerly SR1). It is composed of a Securifor® 4D panel combined with a B Thru type of post with spider fixator.

This classification guarantees validated resistance against low-level intrusion attempts, in accordance with the strict criteria of Issue 8. It ensures reliable and adaptable protection for sensitive sites.

Modular and Reliable Solution

The system combines a Securifor® 4D panel with a B Thru type of post with spider fixator, ensuring a robust installation. Its design guarantees high stability, even on sloped terrain. This versatile system easily adapts to the constraints of various sites.

Protection Against Manual Intrusion

The combination of a narrow-mesh panel and a strong post provides effective defense against vandalism. The 4/6 mm wire prevents climbing or break-ins, while the post resists pulling attempts. The wires are also nearly impossible to cut with standard tools.

Scalable Deterrent Device


Designed for high-security sites, this panel and post system is available up to 5 meters in height. It serves as a real barrier against intrusions. For added protection, it can be paired with alarm or detection systems.

Functionalities



Security level

(when compared to other **high security panel** options)



Post

Section: (depends on the height of the fence):

- 60 x 60 x 2.5 mm
- 60 x 60 x 3 mm
- 80 x 80 x 2 mm
- 80 x 80 x 3 mm
- 100 x 100 x 3 mm
- 120 x 60 x 3 mm
- 120 x 120 x 3 mm

Fixation: Spider fixator are fixed with mushroom head screw M10 + stainless steel washers & break off nuts through the whole post.

B Thru type of post galvanised steel profile, with fixing by means of a spider fixation to accommodate the Securifor® 4D panels.

Reliable Safety Standard

The LPS 1175 Issue 8 standard offers enhanced security thanks to a rigorous classification of resistance levels against intrusions. **The system we offer has been tested and certified** to meet the standard's requirements, allowing for optimal adaptability with different categories of threats, guaranteeing tailor-made protection according to the specific needs of sensitive sites.

Recognized internationally, it constitutes a guarantee of trust for professionals seeking proven and certified solutions to effectively secure their infrastructures.

Panel

Mesh size: 76.2 x 12.7 mm

Horizontal wire diameter: 4 mm

Vertical wire diameter: 4 mm

The 2m and 2m40 SECURIFOR® 4D panels are 2m80 wide and the 3m, 2m and 5m panels are 2m50 wide.

Several panels can be installed one above the other.

Weld strength: 50% of the minimum tensile strength of wire.

Fully tested to comply with the security standard in Europe.

Options

- Posts with welded base plate
- Single, double-welded or bolted vertical extension arms to support three rows of barbed wire available to provide additional security
- Other non-standard height, post lengths and/or sections are available on request

Colours

Green RAL 6005, White RAL 9010, Anthracite RAL 7016 and Black RAL 9005.

Other colours are available on request.

Coating technique



Our coating technology guarantees a long product lifetime even in corrosive environments.

LPS 1175 A1 (Formerly SR1) Rated Fencing Systems						
System Height (mm)	Length of post in concrete (mm)	Length of base plate post (mm)	Section size intermediate posts (mm)	Section size corner posts (mm)	Number of fixation per intermediate post	Number of fixation per corner post
2000	2700	2045	60 x 60 x 2.5	80 x 80 x 2	7	2 x 7
2400	3100	2426	60 x 60 x 3	80 x 80 x 2	9	2 x 9
3000	3800	3036	80 x 80 x 3	80 x 80 x 3	11	2 x 11
4000	5000	4029	120 x 60 x 3	100 x 100 x 3	14	2 x 14
5000	6040	5032	120 x 120 x 3	120 x 120 x 3	18	2 x 18

Saudi Arabia:
6th Floor, Sumou Tower,
Prince Turki Street, Al Yarmouk
Al Khobar-34423
Kingdom of Saudi Arabia

Middle East:
P.O. Box 293517 DAFZA,
Building E 5, Block A 8th Floor,
Office 802

Belgium:
Blokkestraat 34B
8550 Zwevegem
Belgique

USA:
3309 SW Interstate 45,
Ennis, TX 75119

Betafence is the world market leader in fencing solutions, access control and detection for perimeter protection. All Betafence companies and product names are trademarks owned by PRÆSIDIAD Group Limited. Modification in products and assortment are subject to change without prior notice.

Proud to be a PRÆSIDIAD brand. Betafence is part of a global network, working alongside Hesco as a leader in perimeter security systems and solutions. For more information please visit praesidiad.com.

BETAFENCE
Securing What Matters

betafence.com