

# Bekafix® Ultra post

**A higher rigidity profiled post, for medium to high security applications, at an excellent price-quality ratio.**



## Benefits

With the Bekafix Ultra post, all the benefits of the standard Bekafix post are kept, but by increasing the inertia considerably, its application range has become much wider.

- Quick installation
- Base plates maintained directly in between the posts, without any plate holders
- Same accessories as the Bekafix posts
- 10-year guarantee in extreme conditions

## Profile

- Tubular post, profiled in H-shape, cross section of the post: 70 x 44mm, plate thickness: 1.75mm
- Central holes every 15cm for fixing the metal security clips with bolts
- Side punched holes for positioning and fixing of the panels by means of fixing clips
- I/V: 7.29 cm<sup>3</sup>; yield strength: 550MPa; relative strength Bekafix Ultra: 401 compared to 132 for Bekafix posts
- Post cap with hook to hang panels for ease of installation

## Accessories/options

(same as Bekafix post, except for metallic fixators)

- Fixing system: plastic coated metal clip with, as an option, one-way security bolt
- Bekafix installation plier
- Spider fixing for installation of Securifor panels
- Base plate for installation on tiles or concrete floor
- Connection piece to create bent arm for panels or extension
- Single or double bent arms for Bekafix range

## Coating technique



Magnelis® inside and outside and polyester coated (minimum 100 microns).

## Product detail



## Colours

Green RAL 6005, Black RAL 9005, Anthracite RAL 7016 and White RAL 9010. Other colours are available on request.

## Compatible products

- All Nylofor® panels (in superposition) (up to 4m)
- CreaZen® panels
- Securifor® panels (up to 3m)
- Screeno® Line Privacy
- Collfort® Privacy

| Bekafix® Ultra post range |                  |  |                                 |
|---------------------------|------------------|--|---------------------------------|
| Fence height (mm)         | Post length (mm) | Number of fixators per intermediate post | Number of fixators per end post |
| 1930*                     | 2475             | 8  | 4                               |
| 2030                      | 2575             | 8  | 4                               |
| 2430                      | 3175             | 8  | 4                               |
| 3000                      | 3775             | 10                                       | 5                               |
| 4000                      | 4775             | 12                                       | 6                               |

\* The same post can be used for installation in concrete or foot plate. Other heights are available on request

**Europe:** Blokkestraat 34b,  
B-8550 Zwevegem  
Tel: B: +32 56 73 46 46

**USA:** 3309 SW Interstate 45,  
Ennis, TX 75119  
Tel: +1 972 878 7000

**Middle East:** P.O. Box 293517 DAFZA,  
Building E 5, Block A 8th Floor, Office 802  
Tel: +971 04 6091122

**Africa:** B10, Bergriver Business Park,  
Paarl, 7646  
Tel: +27 021 868 7300