

Nylofor® 2D

## **Panels**

The Nylofor 2D are welded mesh panels with double horizontal wires providing high rigidity.

## **Product detail**



## **BENEFITS**

## Very rigid

The panels are rigid thanks to the use of welded mesh in conjunction with double horizontal wires.

## **Long lifetime**

Betafence's coating technology guarantees a long lifetime. After galvanising an adhesion coating is applied for a perfect bond with the polyester coating.

## **Complete system**

The system includes panels in different mesh apertures and heights, posts with adapted fixing systems and a large range of gates. All components guarantee a fast and professional installation.

# **Security level**



# **Applications**



## **Functionalities**





#### Post and fixing systems

The Nylofor 2D system can be used with several posts systems:



#### Nylofor - Twilfix post system

The panels are fixed on the front side of the posts by means of fixators and security bolts. The welded square tubular posts ( $60 \times 60 \text{ mm}$ ) have inserts for fixing the panels and are covered with a plastic cap.

For installation higher than 2.40 m, post section can be 80x60 or 120x60



### Bekafix and Bekafix Ultra post system

The panels are fixed laterally onto the posts and secured with anti-vandal metal security fixators. The H-shape welded tubular posts (70 x 44 mm), are galvanised and PES coated an supplied complete with a polyamide cap and accessories.



#### **D-LOX** post system

The panels are fixed on to the front side of the posts, they are first hung in the premounted metal clamps.



#### **0-LOX post system**

Rigid post system with coverplate or stainless steel fixing plate.

#### **Panels**

The panels have a width of 2500 mm and a height from 630 to 2430 mm. The panels have vertical barbs of 30 mm on one side and are reversible (barbs at top or at bottom).

	Wire diameter		Mesh
Туре	Horizontal	Vertical	
Nylofor 2D	2 x 6 mm	5 mm	200 x 50

#### Gates

The Nylofor 2D system can be completed with Robusta type gates: single or double swing or sliding gates.

#### Privacy system available

Nylofor 2D panels can be filled with Screeno Wave for a full privacy solution.

#### Coating technique

Panels made out of galvanised wires. An adhesion coating is given for a perfect adhesion with the polyester coating (min. 100 micron).

#### Colours

Nylofor 2D is available in green RAL 6005, grey RAL 7016. Other RAL colours are available on request.

ASSORTMENT NYLOFOR 2D			
Fence height - mm	Panels width x height - mm		
630	2500 x 630		
830	2500 x 830		
1030	2500 x 1030		
1230	2500 x 1230		
1430	2500 x 1430		
1630	2500 x 1630		
1830	2500 x 1830		
2030	2500 x 2030		
2430	2500 x 2430		

Europe Blokkestraat 34b B-8550 Zwevegem

Tel: B: +32 56 73 46 46 Tel: NL: 0800 022 76 98 USA 3309 SW Interstate 45 Ennis, TX 75119

Tel: +1 972 878 7000

Middle East P.O. Box 293517 DAFZA, Building E 5, Block A 8th Floor, Office 802 Tel: +971 04 6091122 Africa B10, Bergriver Business Park Paarl, 7646

Tel: +27 021 868 7300