


Bekafix® posts

Product detail



Compatible products

- All Nylofor panels
- CreaZen
- Decofor
- HoriZen Prime

Posts

Profiled posts, polyester coated or galvanised with fixing system to be used with multiple panels.

BENEFITS

- Very attractive symmetrical shape
- Fixing system almost not visible
- Steps for slopes: 2,5 cm
- Ideal for all panels in medium security
- Perfect for installation with concrete plate

Profile

- Tubular post, profiled in "H" shape, plate thickness: 1,25 mm
- With 3 pre-drilled holes for fixing of the special metal security clips with bolts
- With punched holes for positioning and fixing of the panels by means of fixing clips
- Cross section of the post: 70 x 44 mm
- **II/V: 5.28 cm³ | Yield strength: 250 MPa | Relative strength: 132**
- Cap with hook to support panels during installation

Accessories

- Security fixation system: plastic coated metal clip with as an option stainless bolt with nut with break-off head
- Metal or polyamide fixing brackets
- Bekafix installation tongs
- Floor plate
- Connection piece to create bent arm for panels or extension
- Single or double bent arms

Coating technique and colours

Galvanised: inside and outside and polyester coated (minimum 60 microns).
Green RAL 6005 and grey RAL 7016 Other colors are available on request.



ASSORTMENT BEKAFIX® POSTS

Panel height mm	Post length mm		Number of fixators/post (intermediate/corner post*)
	Concrete	Baseplate	
630	1075	675	2 x 2
830	1275	-	2 x 2
1030	1475	1075	2 x 2
1230	1675	1275	2 x 3
1430	1975	-	2 x 3
1530	1975	1575	2 x 3
1630	2175	1675	2 x 3
1730	2175	1775	2 x 3
1830	2475	1875	2 x 4
1930	2475	1975	2 x 4
2030	2575	2075	2 x 4
2230	2775	-	2 x 4
2430	3175	2475	2 x 4

* end post = only half of the numbers of fixators necessary

Europe
Blokkestraat 34b
B-8550 Zwevegem
Tel: B: +32 56 73 46 46

USA
3309 SW Interstate 45
Ennis, TX 75119
Tel: +1 972 878 7000

Middle East
P.O. Box 293517 DAFZA, Building E 5,
Block A 8th Floor, Office 802
Tel: +971 04 6091122

Africa
B10, Bergriver Business Park
Paarl, 7646
Tel: +27 021 868 7300