BETAFENCE



Bekafix® Ultra posts

Posts

A higher rigidity profiled post, for medium to high security applications, at an excellent price-quality ratio.

With the Bekafix Ultra post, all the benefits of the standard Bekafix post are kept, but by increasing the inertia considerably, its application range has become much wider.

. Concrete plates maintained directly in between the posts, without any plate holders Same accessories as the standard Bekafix posts, except for the metallic fixators

Product detail




Profile

BENEFITS

Quick installation

- Tubular post, profiled in "H" shape, cross section of the post: 70 x 44 mm, plate thickness: 1.75 mm
- With central holes every 15 cm, for fixing of the special metal security clips with bolts
- With side punched holes for positioning and fixing of the panels by means of fixing clips
- I/V: 7.29 cm3 | Yield strength: 550 MPa | Relative strength Bekafix Ultra: 401 compared to 132 for Bekafix posts
- · Post cap with hook to hang panels for ease of installation.



Accessories (same as Bekafix Standard post)

- · Fixing system: plastic coated metal clip with, as an option, one-way security bolt
- Bekafix installation plier
- · Spider fixing for installation of Securifor panels

• 10 Years guaranty in Extreme conditions

- · Base plate for installation on tiles or concrete floor
- Connection piece to create bent arm for panels or extension
- · Single or double bent arms for Bekafix range

Compatible products

- All Nylofor panels (in superposition) up to 4 m
- CreaZen panels
- Securifor panels up to 3 m

Coating technique

Magnelis®: inside and outside and polyester coated (minimum 100 microns).



Colors

Green RAL 6005, Black RAL 9005, Anthracite RAL 7016 and White RAL 9010 Other colors are available on request.

BEKAFIX® ULTRA POSTS			
Fence height mm	Post length mm	Number of fixators per intermediate post	Number of fixators per end post
1930*	2475	8	4
2030	2575	8	4
2430	3175	8	4
3000	3775	10	5
4000	4775	12	6

^{*} The same post can be used for installation in concrete or footplate

Other heights available on request

Europe Blokkestraat 34b B-8550 Zwevegem Tel: B: +32 56 73 46 46 **USA** 3309 SW Interstate 45 Ennis, TX 75119 Tel: +1 972 878 7000

Middle East P.O. Box 293517 DAFZA, Building E 5, Block A 8th Floor, Office 802 Tel: +971 04 6091122

Africa B10, Bergriver Business Park Paarl, 7646 Tel: +27 021 868 7300